

# RESIDENTIAL IRON FILTERS



Superior's customized residential iron filters are perfect for removing iron, manganese and hydrogen sulfide.



Model Number	Valve Number	Filter Media	Cubic Feet	Flow Rate (GPM)	Mineral Tank	Shipping Weight (Pounds)
SWGSFBP-1		Greensand	1.0	4.5	9" x 48"	140
SWGSFBP-1.5		Greensand	1.5	5.5	10" x 54"	185
SWGSFBP-1.8		Greensand	1.8	6.0	12" x 48"	225
SWGSFBP-2.5		Greensand	2.5	6.5	13" x 54"	290
SWMTMBP-1		MTM	1.0	4.5	9" x 48"	82
SWMTMBP-1.5		MTM	1.5	5.5	10" x 54"	98
SWMTMBP-1.8		MTM	1.8	6.0	12" x 48"	123
SWMTMBP-2.5		MTM	2.5	6.5	13" x 54"	148
SWBIFBP-1		Birm	1.0	4.5	9" x 48"	100
SWBIFBP-1.5		Birm	1.5	5.5	10" x 54"	125
SWBIFBP-1.8		Birm	1.8	6.0	12" x 48"	155
SWBIFBP-2.5		Birm	2.5	6.5	13" x 54"	190
SW56A10BP-1	5610	*	1.0	*	10" x 54"	75
SW25A10BP-1	2510	*	1.0	*	10" x 54"	75
SW25A10BP-1.5	2510	*	1.5	*	12" x 48"	110
SW25A10BP-2	2510	*	1.8	*	13" x 54"	140
SW25A10BP-2.5	2510	*	2.5	*	14" x 65"	190

- All filters listed above include a bypass
  - Birm or filter-ag filters may require an air injector for oxidation
  - MTM or greensand filters require periodic backwashing with potassium permanganate for oxidation
- \* Based on a water test a customized filter media and corresponding GPM will be determined