

RESIDENTIAL WATER SOFTENERS



The 255/760 Logix on demand control module paired with Superior Water Conditioning system.

- Riser or turbulator style 1" distributor
- 255/760 Logix on-demand automatic control valve
- 15x17x36 275 pound capacity brine tank



	Resin Tank Size	Resin Amount (Cubic Feet)	Salt Setting	Flow Rate (GPM)	Amount of Salt per Regeneration (Pounds)	Capacity (Grains)	Gallons to Regenerate	Approximate Time of Regeneration (Minutes)	Backwash Requirement (GPM)	Shipping Weight (Pounds)
SW2	7" x 44"	0.5	L	7.0	1.5	6,000	23	38	1.2	80
SW2	7" x 44"	0.5	M	7.0	4.5	13,000	29	84	1.2	80
SW2	7" x 44"	0.5	H	7.0	7.5	15,000	31	97	1.2	80
SW3	8" x 44"	0.8	L	7.5	2.5	11,000	34	49	1.5	80
SW3	8" x 44"	0.8	M	7.5	7.0	19,000	47	102	1.5	80
SW3	8" x 44"	0.8	H	7.5	11.0	23,000	50	116	1.5	80
SW4	9" x 48"	1.0	L	9.0	3.5	15,000	43	52	2.0	100
SW4	9" x 48"	1.0	M	9.0	9.0	25,000	49	103	2.0	100
SW4	9" x 48"	1.0	H	9.0	15.0	30,000	53	121	2.0	100
SW5	10" x 54"	1.5	L	11.0	5.0	22,000	44	60	2.5	130
SW5	10" x 54"	1.5	M	11.0	13.5	38,000	57	128	2.5	130
SW5	10" x 54"	1.5	H	11.0	22.5	45,000	67	154	2.5	130

Also available in model SW2BP, 3BP, 4BP and 5BP (same as above with electronic time clock control).